



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6 : B60B 3/14, 27/00, F16B 1/00, 21/10	A1	(11) International Publication Number: WO 96/02396 (43) International Publication Date: 1 February 1996 (01.02.96)
(21) International Application Number: PCT/IT95/00117 (22) International Filing Date: 14 July 1995 (14.07.95) (30) Priority Data: CT94A00012 18 July 1994 (18.07.94) IT (71)(72) Applicants and Inventors: PAPA, Renato [IT/IT]; Via Modigliani, 13, I-95030 Gravina di Catania (IT). AMATO, Paolo [IT/IT]; Via Luna, 21 3° traversa, I-95040 Piano Tavola (IT).	(81) Designated States: JP, US, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.	
(54) Title: QUICK WHEELS REPLACEMENT WITHOUT BOLTS (OR NUTS) (57) Abstract <p>The system consists of a device that has to be installed on car's (or any other vehicle) hubs. The device allows wheels assembling/disassembling without screwing/unscrewing the usual threaded bolts (or nuts). The wheel is clutched to the hub by an easy pushing against the hub, so that the pressure causes the radial extrusion of four pins from the device. Each pin fits in one of four corresponding holes that are made ready in the disc wheel or in a circular groove inside the wheel sleeve. The pins are forced out by the hydraulic thrust of four small rams that are activated by the central sleeve of the disc wheel which slides progressively on the hub. After the assembling completion, the four pins are properly secured. The wheel can be disassembled by manual starting up of the pins release mechanism.</p> <div data-bbox="925 1129 1356 1585" data-label="Image"> </div>		

PCT

WORLD INTELLECTUAL
Property Organization

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)



(51) International Patent Classification⁶ :

B60B 3/14, 27/00, F16B 1/00, 21/10

A1

(43) International Publication Date: 1 February 1996 (01.02.96)

(21) International Application Number: PCT/IT95/00117

(22) International Filing Date: 14 July 1995 (14.07.95)

(30) Priority Data:
CT94A00012 18 July 1994 (18.07.94)

IT

(71)(72) Applicants and Inventors: PAPA, Renato [IT/IT]; Via Modigliani, 13, I-95030 Gravina di Catania (IT). AMATO, Paolo [IT/IT]; Via Luna, 21 3^a traversa, I-95040 Piano Tavola (IT).

(81) Designated States: JP, US, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).

Published


With international search report.

Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

(54) Title: QUICK WHEELS REPLACEMENT WITHOUT BOLTS (OR NUTS)

(57) Abstract

The system consists of a device that has to be installed on car's (or any other vehicle) hubs. The device allows wheels assembling/disassembling without screwing/unscrewing the usual threaded bolts (or nuts). The wheel is clutched to the hub by an easy pushing against the hub, so that the pressure causes the radial extrusion of four pins from the device. Each pin fits in one of four corresponding holes that are made ready in the disc wheel or in a circular groove inside the wheel sleeve. The pins are forced out by the hydraulic thrust of four small rams that are activated by the central sleeve of the disc wheel which slides progressively on the hub. After the assembling completion, the four pins are properly secured. The wheel can be disassembled by manual starting up of the pins release mechanism.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LJ	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

- 1 -

DescriptionQuick wheels replacement
without bolts (or nuts)Technical Field

The system consists of a device that has to be installed on cars (or any other vehicle) hubs. The device allows wheels assembling/disassembling without screwing/unscrewing the usual threaded bolts (or nuts):

Background Art

Changing a wheel is currently requiring a sequence of time consuming operations, i.e.:

- 10 1. bolts (or nuts) unscrewing (normally from 3 to 5 in car's wheel) by means of proper spanner;
2. wheel taking out from hub;
3. wheel putting in and contemporaneous alignment of stud holes with the threaded holes (or studs)
- 15 in the hub;
4. screwing the bolts (or nuts) and fastening them by proper spanner, to the correct torque.

It is widely recognised that the above operations are not simple because of frequent difficulties which have to be faced, e.g.:

- 20 a. to unscrew bolts (or nuts) that requires a significant muscular strength;
- b. to hold the wheel for keeping aligned disc and hub's holes.

25 Moreover, the handling of bolts and spanner causes unpleasant smearing of the hands.

- 2 -

Disclosure of Invention

For obtaining the rapid change of the wheels it is required;

- a: to install the cylinder-shape device on the hub
5 (fig. 1);
- b: to equip the disc wheel (rim) with a central sleeve that is properly shaped to couple with the device (fig. 2).

The proposed system eliminates all the mentioned disadvantages, and allows the wheel replacement in a few simple, time saving operations with no strength required.

The assembling will be carried out with the simple and quick movement which is required to place the wheel on the hub. A moderate physical effort is required
15 only for pushing forward the wheel while it is approaching the hub. The pressure of the disc wheel it self, against the hub, puts in action the mechanism of the device; the four pins will then come out from the device (fig. 3), that is fully matchable with the hub, and
20 will seat in four corresponding holes (or in an holder) made ready in the central sleeve of the disc wheel (rim) (fig. 4):

The pins' extrusion is obtained by hydraulic (oil) thrust of four small rams that are activated by the
25 progressive sliding of the hub into the central sleeve of the disc wheel (rim); the internal surface of the sleeve is shaped on purpose (fig. 5 - 6 - 7):

The oil is housed inside the device (fig. 8) and it
30 is help pressurised by a piston (fig. 9) fitted from the exterior surface of the device. Proper caps make sure the seal of piston, small rams and pins (fig.

- 3 -

7 - 8).

On the internal surface of the sleeve, at one end of special grooves (fig: 12 n: 1), are placed suitable shaped cams (fig: 12 n: 2) which progressively transmit
5 adequate pressure for pushing in the four small rams (fig. 13 n: 1). The movements of the small rams transmit the hydraulic thrust to the pins so that, when the sleeve is completely fitted on the hub, they come quickly
10 off (fig: 13 n: 2) and take position inside the corresponding holes (or groove) of the sleeve (fig: 4) at this time the wheel is tightly fastened to the hub (fig. 14).

The whole assembling operation is just a few seconds long.

15 The effort required is only to lift up the wheel and to approach its central part to the hub. These are operations similar to the current ones that also require the further screwing and fastening of the bolts (or nuts). With the proposed system only a moderate pressure
20 against the hub is required to obtain in a little while assembling and fastening of the wheel.

To avoid the accidental pins release, a suitable safety cap (or hub cover) (fig: 15) will be externally fitted to the wheel. This cap is moulded to have four
25 arms with crescent-shape ends that will plug in suitable narrowing (slot) made in the pins (fig: 16).

To disassemble the wheel it is sufficient to take down the safety (fig: 19) cap and, by means of a proper spanner (fig: 20), to rotate anticlockwise the
30 end part of the device (fig: 18 n: 2). This will cause the release of the ram that holds the hydraulic system pressure, the consequent release of the pins (fig.

- 4 -

18 n: 3) and the wheel loosening:

As previously stated, it is indispensable to have properly shaped circular rims that have been equipped with the specific sleeve, suitable to house the device.

- 5 The hub drives the wheel by means of a frontal joint (with an appropriate number of teeth) or similar devices (such as for example a splined hub and so on): (Fig: 21)

The safety cap may be locked by a key or a clutch (fig: 17)..

- 5 -

Claims

Quick wheel replacement - System for the rapid assembling/
disassembling of vehicle's wheels without use of bolts
(or nuts) and with which the disc wheel is fastened
5 to the hub by means of four pins that come off from
the device and seat inside suitable holes (or a groove)
located in the interior surface of the central
disc wheel's sleeve:

Quick wheel replacement - System for the rapid assembling/
10 disassembling of vehicle's wheels without use of bolts
(or nuts), in which the pins extrusion is obtained
by the hydraulic pressure of the oil housed in the
device:

Quick wheel replacement - System for the rapid assembling/
15 disassembling of vehicle's wheels without use of bolts
(or nuts), in which the disc wheel (rim) insertion
in the hub puts in action four small rams that by means
of the oil contained in the device, transmit an hydraulic
thrust to four pins:

20 Quick wheel replacement - System for the rapid assembling/
disassembling of vehicle's wheels without use of bolts
(or nuts), in which the activation of four small rams
is obtained by suitable cams that are located at one
end of four grooves on the interior surface of the
25 sleeve; the cams movement increases progressively the
thrust concurrently to the progressive sliding of the
sleeve on the hub:

- 6 -

Quick wheel replacement - System for the rapid assembling/
disassembling of vehicle's wheels without use of bolts
(or nuts), in which, after the wheel assembling, to
prevent the accidental release of the pins, a suitable
5 safety cap (or hub cover), moulded with four arms with
crescent end shape, fits in proper narrowing (slot)
made on the pins.

Quick wheel replacement - System for the rapid assembling/
disassembling of vehicle's wheel without use of bolts
10 (or nuts), by which the right hydraulic pressure is
obtained operating from the outside on the piston housed
in the device:


Quick wheel replacement - System for the rapid assembling/
disassembling of vehicle's wheels without use of bolts
15 (or nuts), in which the pins release is obtained by
loosing the piston and by the consequent decrease of
the hydraulic pressure inside the system:

Quick wheel replacement - System for the rapid assembling/
disassembling of vehicle's wheels without use of bolts
20 (or nuts), by which the hub drives the wheel by means
of a frontal joint (with an appropriate number of teeth)
or similar device (such as for example a splined hub
an so on):

The safety cap may be locked by a key or a clutch


1/14

FIG. 01



2/14

FIG. 02







FIG. 04

4/14




FIG. 05




FIG. 06





FIG. 07


FIG. 08

5/14




6/14

FIG. 09




7/14

FIG. 10




8/14

FIG. 11




9/14

FIG. 12




10/14

FIG. 13



11/14



12/14

FIG. 15





FIG. 16




FIG. 17

FIG. 18




FIG. 19






FIG. 20





INTERNATIONAL SEARCH REPORT

Int. Application No
PCT/IT 95/00117

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 B60B3/14 B60B27/00 F16B1/00 F16B21/10

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 B60B F16B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X Y	US,A,3 390 916 (SHELTON) 2 July 1968 see column 1, line 57 - column 2, line 67; figures	1 2
Y	--- PATENT ABSTRACTS OF JAPAN vol. 12 no. 251 (M-718), 15 July 1988 & JP,A,63 038002 (MASAAKI TAKEUCHI) 18 February 1988, see abstract	2
A	--- GB,A,199 218 (EDEN) 12 July 1923 see page 1; figures	1
A	--- FR,E,340 523 (TRENAIL) 21 October 1904 see page 2, line 6 - line 20; figure 1	1
A	--- US,A,1 910 795 (HALL) 23 May 1933 see figures	1
	--- -/-	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- *&* document member of the same patent family

Date of the actual completion of the international search

16 November 1995

Date of mailing of the international search report

27. 11. 95

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax (+31-70) 340-3016

Authorized officer

Vanneste, M

INTERNATIONAL SEARCH REPORT

Int .onal Application No
PCT/IT 95/00117

C(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	DE,C,638 105 (SCHOLZ) 9 November 1936 ---	
A	US,A,4 231 670 (KNOSKI) 4 November 1980 ---	
A	EP,A,0 187 923 (PORSCHE) 23 July 1986 ---	
A	US,A,4 477 121 (ATKINS) 16 October 1984 -----	

INTERNATIONAL SEARCH REPORT

Information on patent family members

Int. Appl. No.
PCT/IT 95/00117

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US-A-3390916	02-07-68	NONE	
GB-A-199218		NONE	
FR-E-340523		NONE	
US-A-1910795	23-05-33	NONE	
DE-C-638105		NONE	
US-A-4231670	04-11-80	NONE	
EP-A-187923	23-07-86	DE-A- 3501240	17-07-86
		JP-A- 61166705	28-07-86
		US-A- 4690462	01-09-87
US-A-4477121	16-10-84	NONE	